OMRON

Automatic Blood Pressure Monitor

Model JPN500 Instruction Manual



Introduction

Thank you for purchasing the OMRON JPN500 Automatic Blood Pressure

The OMRON JPN500 is a compact, fully automatic blood pressure monitor. operating on the oscillometric principle. It measures your blood pressure and pulse rate simply and quickly. For comfortable controlled inflation without the need of pressure pre-setting or re-inflation the device uses its advanced IntelliSense" technology.

Intended Use

This product is designed to measure the blood pressure and pulse rate of people within the range of the designated arm cuff, following the instructions in this instruction manual

It is mainly designed for general household use. Please read the Important Safety Information in this instruction manual before using the unit.

Please follow this instruction manual thoroughly. Please keep for future reference.

For specific information about your own blood pressure, CONSULT YOUR DOCTOR.

Important Safety Information

Please read this section carefully before using the unit.

AWarning: Indicates a potentially hazardous situation which, if not avoided, could result in death or serious injury.

(General Usage)

- DO NOT adjust medication based on measurement results from this blood pressure monitor. Take medication as prescribed by your doctor. Only a doctor is qualified to diagnose and treat High Blood Pressure.
- Consult your doctor before using the device for any of the following conditions: common arrhythmias such as atrial or ventricular premature beats or atrial fibrillation. arterial sclerosis, poor perfusion, diabetes, age, pregnancy, pre-eclampsia, renal diseases.
- Note that PATIENT motion, trembling, shivering may affect the measurement • Do not use the device on the injured arm or the arm under medical treatment.
- Do not apply the arm cuff on the arm while being on an intravenous drip or blood transfusion.
- · Consult your doctor before using the device on the arm with an arteriovenous (A-V) shunt
- Do not use the device with other medical electrical (ME) equipment simultaneously
- Do not use the device in the area the HF surgical equipment, MRI, or CT scanner exists, or in the oxygen rich environment • The air tube or the AC adapter cable may cause accidental strangulation in
- infants • Contains small parts that may cause a choking hazard if swallowed by
- Stop using the unit and consult your doctor if you experience skin irritation or other troubles.

(AC Adapter (optional) Usage)

- Do not use the AC adapter if the unit or the power cord is damaged. Turn off the power and unplug the power cord immediately Plug the AC adapter into the appropriate voltage outlet. Do not use a
- multiple-tar • Never plug in or unplug the power cord from the electric outlet with wet hands
- ▲ Caution: Indicates a potentially hazardous situation which, if not avoided, may result in minor or moderate injury to the user or patient or

(General Usage)

- · Always consult your doctor. Self-diagnosis of measurement results and self-treatment are dangerous.
- · Consult your doctor before using the device for any of the following

damage to the equipment or other property

- If you have had a mastectomy.
- People with severe blood flow problems or blood disorders as cuff inflation can cause bruising. Do not take measurements more than necessary. It may cause bruising due
- to blood flow interference. • If there are any abnormalities during the measurement, remove the arm cuff.
- Do not use this device on infants or persons who cannot express their intentions.
- Do not inflate the arm cuff more than necessary.
- Do not use the unit for any purpose other than measuring blood pressure. • Use only the approved arm cuff for this device. Use of other arm cuffs may result in incorrect measurement results
- Do not use a mobile phone or other devices that emit electromagnetic fields, near the device. This may result in incorrect operation of the device.
- Do not disassemble the monitor or arm cuff. This may cause an inaccurate
- Do not use in a location with moisture, or a location where water may splash on the device. This may damage the device.
- Do not use the device in a moving vehicle (car, airplane).

(Battery Usage)

- Do not insert the batteries with their polarities incorrectly aligned.
- Use only four "AA" alkaline or manganese batteries with this unit. Do not use other types of batteries. Do not use new and used batteries together
- Remove the batteries if the unit will not be used for 3 months or more

(AC Adapter (optional) Usage)

- Fully insert the power plug.
- When disconnecting the power plug, do not pull the power cord. Be sure to hold the power plug
- When handling the power cord, observe the following:
- Do not break it Do not damage.
- Do not forcibly bend or pull Do not tamper with it. Do not bundle during use. Do not twist.
- Do not place under heavy objects. Do not pinch.
- Wipe the dust off from the power plug. • Disconnect the power plug if the product will not be used for a long period of
- · Disconnect the power plug before starting maintenance. • Use only the original AC adapter designed for this unit. Use of unsupported
- adapters may damage and/or may be hazardous to the unit.

General Precautions


1. Overview

Main unit:


Arm cuff:

Display:

- Do not forcibly bend the arm cuff or bend the air tube excessively. • To unplug the air plug, pull on the air plug at the connection with the main unit, not the tube itself.
- Do not apply strong shocks and vibrations to or drop the unit and arm cuff.
- Do not inflate the arm cuff when it is not wrapped around your arm.
- Read and follow the "Important information regarding Electro Magnetic Compatibility (EMC)" in the EMC information provided with this unit. • Do not use the device outside the specified environment. It may cause an
- inaccurate reading. • Dispose of the device, components and optional accessories according to
- applicable local regulations. Unlawful disposal may cause environmental pollution.




A. Display B. START/STOP button C. Memory button



AC adapter)

AC adapter jack (for optional

22 - 32 cm) H. Air plua . Air tube J. Marker



- Q. Irregular heartbeat symbol R. Movement error symbol
- S. Pulse display
- . Deflation symbol
- O. Cuff wrapping guide Note: If your systolic or diastolic
 - pressure is outside the standard range (above 134/84 mmHg) the Heartbeat symbol (1) wil blink. Please refer to Section 3.3. indicates blood pressure out of
- 2. Preparation

K. Memory symbol

N. Low battery symbol

P. Heartbeat symbol

L. Systolic blood pressure

M. Diastolic blood pressure

2.1 Installing/Replacing the Batteries

Remove the battery cover

1. Flashes during measurement.


2. If flashing after measurement

completed or when viewing


results stored in the memory.

recommended range*.

2. Insert 4 "AA" batteries as indicated, into the battery compartment and then replace the battery cover.



- Notes:
- When the depleted battery symbol (the monitor off and remove all the batteries. Replace with 4 new batteries at the same time. Long life alkaline batteries are
- recommended. • The measurement values continue to be stored in memory even after the batteries are replaced.
- The supplied batteries may have a shorter life than new batteries. • Disposal of used batteries should be carried out in accordance with
- the national/local regulations for the disposal of batteries.



3.1 Applying the Arm Cuff

Remove tight-fitting clothing or tight rolled up sleeve from your upper arm. Do not place the arm cuff over thick clothes.

1. Insert the air plug into the air jack securely.


2. Put your arm through the cuff loop

> The bottom edge of the arm cuff should be 1 to 2 cm above the elbow Marker (arrow under the air tube) is centred on the middle of

3. Close the fabric fastener FIRMLY.

vour inner arm.

 When you take a measurement on the right arm, the air tube will be at the side of your elbow. Be careful not to rest your arm on the air tube.



▲ Always consult your doctor. Self-diagnosis of measurement

results and self-treatment are dangerous

• The blood pressure can differ between the right arm and the left arm, and therefore also the measured blood pressure values can be different. Omron recommends to always use the same arm for measurement. If the values between both arms differ substantially. please check with your doctor as to which arm to use for your measurement.

3.2 How to Sit Correctly To take a measurement, you need to be relaxed and comfortably seated, under comfortable room temperature. Avoid bathing, drinking alcohol or caffeine, smoking, exercising or eating 30 minutes before taking a measurement. Also avoid taking measurements during stressful

• Sit in a chair with your legs uncrossed and your feet flat on the floor.

time. Stress raises blood pressure.

- Sit upright with your back straight.
- Sit with your back and arm being supported The arm cuff should be placed on your arm

at the same level as your heart.

3.3 Taking a Reading

▼STAR

the air in the arm cuff.

Remain still while taking a measurement.

The arm cuff will start to inflate automatically

Press the START/STOP button.

250

expected systolic pressure.

measurement.

Do not apply more pressure than necessary.

Error Display	Cause	Remedy
\bigcirc	Irregular heartbeat is detected.	Remove the arm cuff. Wai 2 - 3 minutes and then tak another measurement. Repeat the steps in sectio 3.3. If this error continues appear, contact your docto
<i>"</i> 凸»	Movement during measurement.	Carefully read and repeat the steps in section 3.3.
)	Cuff is not applied correctly.	Apply the arm cuff correctl Refer to section 3.1.
	The batteries are low.	Recommend to replace 4 batteries with new ones at this time. Refer to section 2.1.
	The batteries are depleted.	Immediately replace the 4 batteries with new ones. Refer to section 2.1.
E 1	Air plug disconnected.	Insert the plug securely. Refer to section 3.1.
	Arm cuff not applied correctly.	Apply the arm cuff correctl Refer to section 3.1.
	Air is leaking from the arm cuff.	Replace the cuff with the new one. Refer to Chapter 5.
53	Movement during measurement and the arm cuff has not been inflated sufficiently.	Repeat measurement. Remain still and do not tal during measurement. Refer to section 3.3.
		If "E2" appears repeatedly inflate the cuff manually until it is 30 to 40 mmHg above your previous measurement result. Refer to section 3.3.
63	The arm cuff was inflated above 299 mmHg when inflating the cuff manually.	Do not inflate the cuff above 299 mmHg. Refer to section 3.3.
E٩	Movement during measurement.	Repeat measurement. Remain still and do not tal during measurement. Refer to section 3.3.
85	Clothing is interfering with the arm cuff.	Remove any clothing interfering with the arm cur Refer to section 3.1.
Er	Device error.	Contact your local OMROI representative.

4. Troubleshooting and Maintenance


Problem	Cause	Remedy
	Arm cuff not applied correctly.	Apply the arm cuff correctly. Refer to section 3.1.
The reading is extremely low (or high).	Movement or talking during measurement.	Remain still and do not talk during measurement. Refer to section 3.3.
	Clothing is interfering with the arm cuff.	Remove any clothing interfering with the arm cuff. Refer to section 3.1.
Arm cuff pressure does not rise.	The air tube is not securely connected into the main unit.	Make sure that the air tube is connected securely. Refer to section 3.1.
does not rise.	Air is leaking from the arm cuff.	Replace the arm cuff with a new one. Refer to Chapter 5.
Arm cuff deflates too soon.	The arm cuff is loose.	Apply the cuff correctly so that it is firmly wrapped around the arm Refer to section 3.1.
Cannot measure or readings are too low or too high.	The arm cuff has not been inflated sufficiently.	Inflate the cuff so that it is 30 to 40 mmHg above your previous measurement result. Refer to section 3.3.
Nothing happens	The batteries are empty.	Replace the batteries with new ones. Refer to section 2.1.
when you press the buttons.	The batteries have been inserted incorrectly.	Insert the batteries with the correct (+/-) polarity. Refer to section 2.1.
Other problems.	 Press the START/STOP button and repeat measurement. If the problem continues, try replacing the batteries with new ones. If this still does not solve the problem, contact your local OMRON representative. 	

4.3 Maintenance

To protect your unit from damage, please observe the following:

- temperatures, humidity, moisture or direct sunlight. • Do not fold the cuff or tubing tightly.
- · Do not disassemble the unit.
- (for example, dropping the unit on the floor).
- Do not wash the arm cuff or immerse it in water.

 - the arm cuff.
 - occurs, consult your local OMRON representative.



 The unit should be cleaned with a soft, dry cloth. • Use a soft, moistened cloth and neutral soap to clean the arm cuff.

Note: Read and follow the "Correct Disposal of This Product" in the Technical Data Section when disposing of the device and any used accessories or optional parts.

Calibration and Service

- every two years to ensure correct functioning and accuracy. Please consult your local OMRON

4.4 Storage

Store the device and the components in a clean, safe location.

representative.

- **1.** Unplug the air plug from the air jack.
- **2.** Gently fold the air tube into the arm cuff.
- · Do not bend the air tube excessively. · Do not store the unit in the following situations: - If the unit is wet.
- sunlight, dust or corrosive vapors such as bleach
- angle

5. Optional Parts

Small Cuff HEM-CS24 Arm circumference 17 - 22 cm



22 - 32 cm

AC Adapter S



- Please use Adapter [60110HW5SW] in Taiwan, Adapter [6V06ASW-KA] in Korea. • Please check with your local OMRON representatives for the
- appropriate optional parts.

Using the Optional AC Adapter

- **1.** Insert the AC adapter plug into the AC adapter jack on the rear side of the main unit.
- 2. Plug the AC adapter into an electrical outlet.

To disconnect the AC adapter, unplug the AC adapter from the electrical outlet first and then remove the AC adapter plug from the main unit.


Note: Wait 2-3 minutes before taking another blood pressure measurement. Waiting between readings allows the arteries to return to their prior condition to taking the blood pressure

Do not subject the main unit and the cuff to extreme

• Do not subject the unit to strong shocks or vibrations • Do not use volatile liquids to clean the main unit. • Do not use petrol, thinners or similar solvents to clean

· Do not carry out repairs of any kind yourself. If a defect

• The accuracy of this blood pressure monitor has been carefully tested and is designed for a long service life. It is generally recommended to have the unit inspected




- Locations exposed to extreme temperatures, humidity, direct - Locations exposed to vibrations, shocks or where it will be at an



Arm circumference







6. Technical Data

Product Description Model Display Measurement Method Measurement Range

Accuracy

Inflation Deflation Memory IP classification Rating Power Source

Battery Life

Durable period (Service life)

Applied Part

Protection Against Electric Shock

Operating conditions conditions Console Weight Cuff Weight **Outer Dimensions** Cuff Dimensions

Cuff/ Tube Material Package Contents

- Subject to technical modification without prior notice. • This device is clinically investigated according to the requirements of ISO 81060-2.2013
- IP classification is degrees of protection provided by enclosures in accordance with IEC 60529. This device is protected against solid foreign objects of 12 mm diameter and greater such as a finger.

C€0197

- This device fulfils the provisions of EC directive 93/42/EEC (Medical Device Directive).
- This blood pressure monitor is designed according to the European Standard EN1060, Non-invasive sphygmomanometers Part 1: General Requirements and Part 3: Supplementary requirements for electromechanical blood pressure measuring systems.
- This OMRON product is produced under the strict quality system of OMRON HEALTHCARE Co., Ltd., Japan. The core component for OMRON blood pressure monitors, which is the Pressure Sensor, is produced in Japan.

Correct Disposal of This Product

This marking shown on the product or its literature, indicates that it should not be disposed of, with other household wastes at the end of its working life. To prevent possible harm to the environment or human health from uncontrolled waste disposal, please separate this product from other types of wastes and recycle it responsibly to promote the sustainable reuse of material resources.



lousehold users should contact either the retailer where they purchased this product, or their local government office, for details of where and how they can return this item for environmentally safe recycling

Business users should contact their supplier and check the terms and conditions of the purchase contract. This product should not be mixed with other commercial waste for disposal

Manufacturer	OMRON HEALTHCARE Co., Ltd. 53, Kunotsubo, Terado-cho, Muko, KYOTO, 617-0002 JAPAN
EC REP	OMRON HEALTHCARE EUROPE B.V. Scorpius 33, 2132 LR Hoofddorp, THE NETHERLANDS
Asia Pacific HQ	OMRON HEALTHCARE SINGAPORE PTE LTD. 438A Alexandra Road, #05-05/08, Alexandra Technopark, Singapore 119967 www.omronhealthcare-ap.com
Production facility	OMRON HEALTHCARE Co., Ltd. Matsusaka Factory Mie, JAPAN

Made in Japan

Automatic Blood Pressure Monitor .IPN500 LCD Digital Display Oscillometric method Pressure: 0 to 299 mmHg Pulse: 40 to 180 beats/ min. Pressure: ±3 mmHg Pulse: ±5% of display reading Fuzzy-logic controlled by electric pump Automatic pressure release valve 60 measurements IP 20 DC6V 4W 4 "AA" batteries 1.5V or AC adapter (optional, INPUT AC100-240V 50/60Hz 0 12A) Approx, 1000 measurements (using new alkaline batteries) Monitor: 30000 times Cuff: 10000 times



Internally powered ME equipment (When using only the batteries)

= Class II ME equipment (Optional AC adapter)

+10 to +40°C / 30 to 85% RH / 700 to 1060 hPa Storage and transport -20 to +60°C / 10 to 95% RH / 700 to 1060 hPa

> Approx. 250g without batteries Approx. 130g Approx. 103 (w) mm × 80 (h) mm × 129(l) mm Approx. 145 mm × 466 mm (Cuff: arm circumference 22 to 32 cm) Nylon, polyester, polyvinyl chloride Main unit, arm cuff, instruction manual, EMC information, battery set

(Waste Electrical & Electronic Equipment)