



HL168KS

FEATURES:

- Personal Target Limits Function
- Irregular Heartbeat Detector
- 30 memory x 3 users (90 memory total)

SPECIFICATIONS

Model number	HL168KS
Measurement method	Oscillometric
Measurement range	Pressure: 0 ~ 300 mmHg, Pulse: 40 ~ 199 beats/minute
Accuracy	Pressure: ± 3 mmHg, Pulse: $\pm 5\%$ Max.
Inflation	Automatic inflation (air pump)
Deflation	Automatic air release control valve
Display	Liquid Crystal Display
Memory	30 memory x 3 users (90 memory total)
Unit dimensions	L x W x H: 84.8 x 68 x 33 mm (3.34 x 2.68 x 1.3 inch)
Unit weight	162 $\pm$ 5 g (5.71 $\pm$ 0.17 oz) (Excluding batteries)
Cuff size	135 ~ 195 mm (5.3 ~ 7.7 inch)
Storage/Transportation environment	Temperature: -20 ~ 70°C (-4 ~ 158°F), Humidity: $\leq 90\%$ R.H.
Operation environment	Temperature: 10 ~ 40°C (50 ~ 104°F), Humidity: 15 ~ 90% R.H.
Power supply	AAA (1.5V) alkaline battery x 2
Battery life	Approx. 250 measurements
Auto power off	1 minute after last button operation
Accessories	Instruction manual, 2 AAA alkaline batteries, Storage case

These specifications are subject to change without notice for purpose of improvement.