



HL868AF

FEATURES:

- Xrystal LCD Technology
- Thin line, Lightweight Design
- Personal Target Limits Function
- Irregular Heartbeat Detector
- Average of last 3 measurements
- 90 memory x 2 users (180 memory total)

SPECIFICATIONS

Model number	HL868AF
Measurement method	Oscillometric
Measurement range	Pressure: 0 ~ 300 mmHg, Pulse: 40 ~ 199 beats/minute
Accuracy	Pressure: ± 3 mmHg, Pulse: $\pm 5\%$ Max.
Inflation	Automatic inflation (air pump)
Deflation	Automatic air release control valve
Display	Liquid Crystal Display
Memory	90 memory x 2 users (180 memory total)
Unit dimensions	L x W x H: 111 x 100 x 183 mm (4.37 x 3.96 x 7.21 inch)
Unit weight	302 $\pm$ 10 g (10.65 $\pm$ 0.35 oz) (Excluding batteries)
Cuff size	23 ~ 43 cm (9 ~ 17 inch)
Storage / Transportation environment	Temperature: -20 ~ 70°C (-4 ~ 158°F) Humidity: $\leq 90\%$ R.H.
Operation environment	Temperature: 10 ~ 40°C (50 ~ 104°F) Humidity: 15 ~ 90% R.H.
Power supply	1.5V (AA) alkaline batteries x 4; Or 6V/1A DC AC Adapter(Optional)
Battery life	Approx. 300 measurements
Auto power off	1 minute after last button operation
Accessories	4 AA alkaline batteries, Arm cuff with tube, 6V/1A DC AC Adapter(Optional) Instruction manual, Pouch, Gift box

These specifications are subject to change without notice for purpose of improvement.