

K-jump®

Automatic Upper Arm Blood Pressure Monitor



KP-6931



KP-6930
(Multi-user)

Specifications

Model	KP-6930	KP-6931
Measuring Range	20 ~ 300 mmHg 40 ~ 200 pulse/minute	
Resolution	1 mmHg	
Accuracy	±3 mmHg or 2% (pressure) ±5% of readings (pulse rate)	
Measuring Method	Oscillometric method	
Operation Key	3 keys: I/O, M, U	One key: I/O
Display	Liquid crystal display	
Inflation	Micro rolling pump	
Exhaust	Electrical Solenoid Valve	
Memory	2x50, 3x33, 4x25, or 5x20 sets	Last memory
Time	Displaying date, time and year	
Operation Condition	Temperature: 10°C ~ 40°C (50°F ~ 104°F) Relative Humidity: less than 85%	
Storage Condition	Temperature: -10°C ~ +50°C (+14°F ~ +122°F) Relative Humidity: less than 85%	
Power Source	6Vdc; "AA" type battery x 4 or AC/DC power input	
Battery Life	Around 250 measurements(alkaline batteries)	
Low Battery Indication	Replace the batteries if the low battery indicator appears	
Auto Off	Automatically after 150 seconds without operation	
Size	140 x 130 x 70 mm	
Weight	406g w/ batt.	405g w/ batt.
Standard	Complies with EN 1060-1, -3 and ANSI/AAMI SP10:2002	

Specifications are subject to change for improvement without notice.

Accessories:

- AC/DC adapter (optional)

K-jump Health Co., Ltd.

No.56, Wu Kung 5th Rd., New Taipei Industrial Park,

New Taipei City 24890, Taiwan

Tel: 886-2-22991378 Fax: 886-2-22991386

E-mail: service@kjump.com

http://www.kjump.com



CE 0197

- This is ideal for use in a family of up to five members. Each family member's blood pressure data is saved in individual data bank.



HealthCare at Home

We Care for Your Health