

K-jump®

Automatic Upper Arm Blood Pressure Monitor



KP-7770

Specifications

Model	KP-7770
Measuring Range	20 ~ 300 mmHg 40 ~ 200 pulse/minute
Resolution	1 mmHg
Accuracy	±3 mmHg or 2% (pressure) ±5% of readings (pulse rate)
Measuring Method	Oscillometric method
Operation Key	Three Keys: Power/Start, Memory, User
Display	Liquid crystal display + color backlight+W.H.O Indicator
Inflation	Micro rolling pump
Exhaust	Electrical Solenoid Valve
Memory	2x50, 3x33, 4x25, or 5x20 sets
Time	Displaying date, time and year
Operation Condition	Temperature: 10°C ~ 40°C (50°F ~ 104°F) Relative Humidity: less than 85%
Storage Condition	Temperature: -10°C ~ +50°C (+14°F ~ +122°F) Relative Humidity: less than 85%
Power Source	6Vdc; "AA" type battery x 4 or AC/DC power input
Battery Life	Around 250 measurements(alkaline batteries)
Low Battery Indication	Replace the batteries if the low battery indicator appears
Auto Off	Automatically after 150 seconds without operation
Size	142 x 138 x 63 mm
Weight	Approx. 480g (with battery)
Standard	Complies with EN 1060-1, -3 and ANSI/AAMI SP10:2002

Specifications are subject to change for improvement without notice.

Accessories:

•AC/DC adapter (optional)

K-jump Health Co., Ltd.

No.56 Wu Kung 5th Rd., WuKu Industrial Park,
Taipei Hsien, Taiwan 248
Tel: 886-2-22991378 Fax: 886-2-22991386
E-mail: service@kjump.com.tw
http://www.kjump.com.tw



CE 0197

3 Modes of
Measurement

MOMI
Regular
Doctor

Jumbo
DISPLAY

LCD

iPD



Fuzzy
Logic



Optional Functions:

Talking



PC-Link



W.H.O.
Indication

High
Normal High
Normal

Colored
Backlight

LCD



HealthCare at Home
We Care for Your Health