



servocare
NÜTZLICHES FÜR DEN ALLTAG 

Servocare ABPM blood pressure monitor

24h mobile blood pressure monitor for doctor's office or clinic. Simple and fast handling and intuitive software usability makes the Servocare ABPM monitor a reliable tool for the diagnosis ...

Description for Servocare ABPM blood pressure monitor

24h mobile blood pressure monitor for doctor's office or clinic. Simple and fast handling and intuitive software usability makes the Servocare ABPM monitor a reliable tool for the diagnosis in daily routine.

The particularly gentle „Smart Inflation“ measuring procedure ensures a very high level of safety and patient acceptance. The measuring system with two independent processors guarantees reliable results. The robust housing and the easy-to-clean cuffs guarantee trouble-free operation.

Product advantages:

- Easy handling and high measuring quality
- Gentle and fast blood pressure measurement
- 24 h- / 48 h monitoring or spot measurement
- Day- / Night button for the exact allocation of the measured values
- Interface to most current practice management programs via GDT
- Budget-saving operation via inexpensive AA batteries or rechargeables

The evaluation provides information on:

- White coat hypertension
- Masked hypertension
- Abnormal blood pressure
- Day-night rhythm (variability is prognostically interesting)
- Suspected secondary hypertension
- Precise Dipper / Non-Dipper assignment

Technical specifications:

Measuring method: oscillometric measurement

Measuring range Systolic: 60 mmHg to 260 mmHg

Measuring range Diastolic: 30 mmHg to 195 mmHg

Accuracy: ± 3 mmHg over the entire display range

Pulse measurement: 30 to 200 beats per minute

Static pressure range: 0 to 300 mmHg

Measurement logs: 4 freely editable daily and night intervals

(5/10/25/20/30/60 and 120 minutes)

Memory Capacity: max. 400 measurements

Battery capacity: approx. 300 measurements

Operating temperature: + 5 °C to + 40 °C

Operating humidity: <80% non-condensing

Storage ambient: -20 °C to + 50 °C and 15% to 90% humidity

Dimensions: 113 x 75 x 260 mm

Weight approx.: 170g without batteries

Power supply: 2x AA-Mignon 1,5 Volt alkaline

2x Ni-MH AA-Mignon with 1.2 Volt / 2300 mAh each

Interfaces: USB / IRDA / Bluetooth

Type	SU	REF
ABPM blood pressure monitor	1 piece	H7 600