



A new outlook on vital signs — the SureSigns VS2⁺.

Seeing is believing when it comes to the enhanced SureSigns VS2⁺ monitor. With features designed to make taking vital signs easy, the VS2⁺ gives your staff the flexibility and freedom they need to spend more time with their patients. From the easy-to-read viewing area, oversized buttons to the all-new pleth waveform display and intuitive navigation, the VS2⁺ provides the information you need when you need it and maximizing the time spent at the bedside. And with wireless capability and data export in HL7 format, the VS2⁺ provides reliability, peace-of-mind — and patient records in record time.



Internal wireless (802.11 a/b/g) optional.

Oral temperature in just four seconds.

Bright, color backlit 4.3" LCD screen.

2D bar-code scanner programmable for multiple ID fields.

Oversized, one-touch NBP on/off button.

NBP modes, including auto intervals, user-defined interval program and manual start/stop.

Pleth waveform display.

Time-sync network clock.

Confirmation of export records easily seen in green.

Stores up to 100 patient records.

Uses the same supplies as all Philips monitors.

PHILIPS
sense and simplicity

Features built around you

LAN/serial data export

in HL7 format.

AC power input

with power cord clip.

Nurse call

output to assist with alarm recognition.

Sturdy handle

and rugged housing for easy portability.

Philips SpO₂ technology

SpO₂ includes a FAST-based

SpO₂ algorithm and is

compatible with a wide

variety of adult, pediatric

and neonatal sensors.

USB port

for easy software upgrades and data export.

Optional integrated strip

recorder for convenient

documentation.

Lithium ion battery.



New premium rollstand includes an easy-to-clean molded basket that can swivel for easy positioning in tight spaces, and dedicated sections for accessories such as bar code scanner, cleaning wipes, NBP cuffs, extra disposable temperature covers and the SpO₂ sensor.

| Product Specifications | |
|------------------------|---|
| Width, Height, Depth | W: 18.4 cm (8.1"), H: 20.5 cm (7.2"), D: 15.0 cm (5.9") |
| Weight | 2.0 kg (4.3 lbs), including battery, recorder, temperature module and wireless |
| Screen | 10.9 cm (4.3") WQVGA TFT-AM LCD display |
| NBP | <ul style="list-style-type: none"> Oscillometric using stepwise deflation pressure Adult Measurement Range: <ul style="list-style-type: none"> Systolic: 30–270 mmHg (4.0–36.0 kPa) Diastolic: 10–245 mmHg (1.3–32.7 kPa) MAP: 20–255 mmHg (2.7–34.0 kPa) Pediatric Measurement Range: <ul style="list-style-type: none"> Systolic: 30–180 mmHg (4.0–24.0 kPa) Diastolic: 10–150 mmHg (1.3–20.0 kPa) MAP: 20–160 mmHg (2.7–21.3 kPa) Neonatal Measurement Range: <ul style="list-style-type: none"> Systolic: 30–130 mmHg (4.0–17.0 kPa) Diastolic: 10–100 mmHg (1.3–13.3 kPa) MAP: 20–120 mmHg (2.7–16.0 kPa) NBP Intervals: <ul style="list-style-type: none"> Automatic measurements at intervals of 1, 2, 3, 5, 10, 15, 30, 60, 90 or 120 minutes Up to 1 interval can be defined |
| SpO ₂ | <ul style="list-style-type: none"> Measurement Range: 0%–100% Accuracy: Depends on Sensor |
| Temperature | <ul style="list-style-type: none"> Modes: Predictive and Monitored Probe Sites: Oral, Rectal or Axillary Range: <ul style="list-style-type: none"> Monitored Mode: 26.7°C–43.3°C (80°F–110°F) Predictive Mode: 34.4°C to 40.6°C (93.9°F–105°F) Accuracy: ±0.1°C (±0.2°F) in Monitored mode |
| Battery | <ul style="list-style-type: none"> Lithium ion, 10.8–11.1 V, 2150–2300 mAh Operating Time: >4.5 hours, with continuous SpO₂ and NBP interval measured every 15 minutes |
| Data Output | <ul style="list-style-type: none"> HL7 format, via Ethernet port Serial data |
| Patient Type | Adult, Pediatric, Neonatal |

| Also Available | To Order |
|------------------------------|--------------|
| SureSigns Premium Rollstand | 989803176601 |
| SureSigns Standard Rollstand | 989803144001 |
| SureSigns Value Rollstand | 989803175861 |
| Wall Mount | 989803144011 |
| 2D Bar Code Reader and Mount | 989803147821 |
| Serial Interface Adapter | 989803159601 |
| Tabletop Base | 989803176261 |

| Ordering Information | |
|--|--------|
| NBP, SpO ₂ | 863278 |
| • Standard accessories: Adult cuff; NBP tubing; adult finger SpO ₂ sensor, reusable | A01 |
| • No accessories | A02 |
| • Recorder accessories: 5 rolls of recorder paper | R01 |
| • Predictive temperature: Oral temperature probe; 1 box temperature probe covers | T01 |
| NBP, SpO ₂ , Wireless | 863279 |
| • Standard accessories: Adult cuff; NBP tubing; adult finger SpO ₂ sensor, reusable | A01 |
| • No accessories | A02 |
| • Recorder accessories: 5 rolls of recorder paper | R01 |
| • Predictive temperature: Oral temperature probe; 1 box temperature probe covers | T01 |



asimpleswitch.com



SureSigns VS2+ has tested compatible with Cisco Compatible Extensions, Version 4. Go to www.cisco.com/go/compatibledisclaimer for complete disclaimer.

Please visit www.philips.com/suresigns for more information.



© 2012 Koninklijke Philips Electronics N.V.
All rights are reserved.

Philips Healthcare reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

Philips Healthcare is part of Royal Philips Electronics

www.philips.com/healthcare
healthcare@philips.com

Printed in The Netherlands
4522 962 87351 * JUN 2012