

TD-4183

BLOOD GLUCOSE MONITORING SYSTEM



±15mg/dL & ±15%

FEATURES

- 20-65% HCT range
- Individual target range
- 1000 memory sets



SPECIFICATIONS

Enzyme Type	GDH-FAD
Sample Size	0.5 µL
Reaction Time	6 second
Measurement Range	20 ~ 650mg/dL (1.1 ~ 36.1mmol/L)
Hematocrit Range	20% - 65%
Precision	SD < 5mg/dL (0.278mmol/L) at < 100mg/dL (5.55mmol/L); CV < 5% at 100mg/dL (5.55mmol/L)
Accuracy	±15mg/dL if < 100mg/dL; ±15% if ≥ 100mg/dL
Ketone Warning	YES
Communication	Strip Port Communication
Power Source	AAA x 1
Memory Capacity	1000 sets
Day Average	7, 14, 21, 28, 60, 90 days
Daily Alarm	4 daily alarms
Dimension	90.3 (L) x 52.3 (W) x 18 (H) mm
Weight	46.4 g (without battery)
Operating Condition	8°C (46.4°F) ~ 45°C (113°F)
Storage Condition	-20°C (-4°F) ~ +60°C (140°F) (Meter); 2°C (35.6°F) ~ 30°C (86.0°F) (Strip)
Units per Carton	30
Carton Size	340 (L) x 290 (W) x 383 (H) mm
Cross Weight per Carton	7.3 kg

Accessories

Model	Specification
BG-ACC-001	Bluetooth dongle
BG-ACC-002	USB cable



www.taidoc.com

TaiDoc Technology Corp.

B1-7F., No.127, Wugong 2nd Rd., Wugu Dist.,
New Taipei City 24888, Taiwan
Tel : +886-2-6625-8188 Fax : +886-2-6625-0288