

# TD-4267

## BLOOD GLUCOSE MONITORING SYSTEM



### FEATURES

- Strip eject function
- 7, 14, 21, 28, 60, 90 day average function
- Before / after meal (AC/PC) presetable
- Ketone warning



### SPECIFICATIONS

Enzyme Type	GOD
Sample Size	0.5 $\mu$ L
Reaction Time	5 seconds
Measurement Range	20 ~ 600mg/dL (1.1 ~ 33.3mmol/L)
Hematocrit Range	30%-55%
Precision	SD < 5 mg/dL (0.278 mmol/L) at < 100mg/dL (5.55 mmol/L); CV < 5% at 100mg/dL (5.55 mmol/L)
Accuracy	$\pm$ 15mg/dL if < 100mg/dL : $\pm$ 15% if $\geq$ 100mg/dL
Ketone Warning	Yes
Communication	Mini USB
Power Source	CR2032 * 1
Memory Capacity	450 Sets
Day Average	7,14,21,28,60,90 Days
Daily Alarm	4 daily alarms
Dimension	90.0 (L) x 55.0 (W) x 18.0 (H) mm
Weight	49g (Without Battery)
Operating Condition	10°C (50°F) ~ 40°C (104°F)
Storage Condition	-20°C (-4°F) ~ +60°C (140°F) (Meter); 4°C (39.2°F) ~ 40°C (104°F) (Strip)
Units Per Carton	30
Carton Size	397 (L) x 385 (W) x 436 (H) mm
Cross Weight Per Carton	12.7 kg



www.taidoc.com

TaiDoc Technology Corp.

B1-7F., No.127, Wugong 2nd Rd., Wugu Dist.,  
New Taipei City 24888, Taiwan  
Tel : +886-2-6625-8188 Fax : +886-2-6625-0288