

TD-4278

BLOOD GLUCOSE MONITORING SYSTEM



±15mg/dL & ±15%

5 Sec, 1.0 µL

Display Screen

Strip-Ejection



FEATURES

- HCT Range: 0% ~ 70%
- Strip indication light
- Ketone Warning (≥ 240 mg/dL)
- USB Data transmission



SPECIFICATIONS

| | |
|-------------------------|--|
| Enzyme Type | GDH-FAD |
| Sample Size | 1.0 µL |
| Reaction Time | 5 seconds |
| Measurement Range | 10-700 mg/dL (0.56-38.89mmol/L) |
| Hematocrit Range | 0%-70% |
| Precision | ±5% with respect to Standard |
| Accuracy | ±15mg/dL if ≤ 100 mg/dl; ±15% if >100 mg/dL |
| Ketone Warning | Yes |
| Communication | Mini USB (HID) |
| Power Source | 2 x AAA |
| Memory Capacity | 400 sets |
| Day Average | 7, 14, 21, 28, 60, 90 Days |
| Daily Alarm | 4 daily alarms |
| Dimension | 95.5 (L) x 57 (W) x 15 (H)mm |
| Weight | 80.4 g (with battery) |
| Operating Condition | 10°C~40°C, below 85% R.H. |
| Storage Condition | -20 °C ~ +60 °C (Meter); 2°C ~ 32°C (Strip) |
| Units Per Carton | 30 |
| Carton Size | 405 (L) x 390 (W) x 365 (H) mm |
| Cross Weight Per Carton | 12.56 kg |



www.taidoc.com

TaiDoc Technology Corp.

B1-7F., No. 127, Wugong 2nd Road, Wugu Dist.,
New Taipei City 24888, Taiwan
Tel : +886-2-6625-8188 Fax : +886-2-6625-0288